



→ Job Details

Client
Reference No.
Project
Date

→ Specifications

Substrate: Woodhouse Weatherproof (R) Pink Primed Pine

New/Repaint: New Quality: Premium

Interior/Exterior: Exterior
Surface Preparation

Confirm that the timber is Woodhouse Weatherproof. The surface should be clean, dry and free from all dirt, dust, grease, oil and any other surface contamination. Prime bare areas, including cut ends and joints with a suitable primer. Follow instructions provided with the timber by the Woodhouse Weatherproof supplier.

1st coat: Taubmans All Weather Gloss Acrylic (D331)

Application: Brush, Roller	Spreading Rate sqm/litre: 14
Reducer/Washup: Water	Recoat Time: 2
Dry Film Thickness : 0	

2nd coat: Taubmans All Weather Gloss Acrylic (D331)

Application: Brush, Roller	Spreading Rate sqm/litre: 14
Reducer/Washup: Water	Recoat Time: 2
Dry Film Thickness : 0	

DISCLAIMER

The technical information and suggestions for use and application presented herein represent the best information available to use and are believed to be reliable. They should not, however, be construed as controlling suggestions and there is no warranty of performance of our materials either expressed or implied. We urge that users of our materials conduct confirmatory tests to determine that final suitability for their specific end users.